

ATTENTION: RECHARGEABLE BATTERY,
FOR 30 HOURS CONTINUOUS WORKING




HIGH PRECISION DIGITAL INDICATORS


IP54
WATERPROOF

ABSOLUTE ENCODER, THE ORIGINAL
DATA REMAINS AFTER POWER OFF


analog pointer



warning when over tolerance



max./min./TIR






2136-10




2136-25



2136-50



- IP54 dust/waterproof (when cap is lifted, no dust/waterproof)
- Absolute encoder, the original data remains after power off
- Automatic power off
- Reading in digital and analog
- Display can be rotated by 270°
- Button function: on/off, zero setting, data preset, tolerance Go and No-Go display, data hold, mm/inch, measuring direction change, max./min./TIR, absolute/incremental measurement, data output
- Data output with USB cable (keyboard format), cable length 1.8 meters, single and continuous transmission (the fastest data output is 40 pcs per 10s)
- Power: rechargeable battery, for 30 hours continuous working



display can be rotated
(counterclockwise 270°)



pull cap to
lift point

spindle lift knob is included



Resolution 0.0005mm/0.00002"

Code	Range	Accuracy	Hysteresis	Maximum measuring force	cap	Remark
2136-10*	0-12.7mm/0-0.5"	2µm	1.5µm	1.5N	can lift	flat back
2136-25*	0-25.4mm/0-1"	2µm	1.5µm	1.8N	can lift	flat back
2136-50*	0-50.8mm/0-2"	4µm	2µm	2.3N	can lift	flat back

*Supplied with manufacturer inspection certificate