

## PORTABLE SPARK DIRECT READING SPECTROMETER CODE OES-P200



- Widely used in metallurgy, foundry, machining, automobile manufacturing, metal processing, furnace testing, etc.
- Ability to accurately analyze the elemental content of metallic materials such as C, P, S, B, etc.
- Automatically eliminates spectral drift due to temperature and pressure changes for accurate measurements
- Ability to add desired measurement curves without adding hardware
- Unique jet electrode technology, can save the use of argon gas, reduce the use of costs
- Replaceable lithium batteries, long battery life, hundreds of consecutive excitation times, to ensure the integrity of the field work
- The instrument is easy to carry, analysis is not limited, more convenient to complete outdoor work

### STANDARD DELIVERY

Main unit	1 pc
Computer	1 pc
Analysis software	1 pc
Battery	2 pcs
Electrode brush (OES-T350-BR)	2 pcs
Pressure valve	1 pc
Mobile cart	1 pc
Charger	1 pc
Consumable and spare parts	1 set*

\*Including lens, mirror paper, wrench, air connection line and other common consumables

### OPTIONAL ACCESSORY

Spectral sample grinder	OES-MY100
-------------------------	-----------



spectral sample grinder (optional)

## SPECIFICATION

Curves	Standard curve	low and medium alloy steel (A1), chrome/nickel stainless steel (A2)
	Customized curve	curves can be added or customized for special base materials (Ni, Mg, Zn, etc.)
Optical system	Detector	high performance CMOS
	Optical system construction	paschen-range double optical chamber structure
	Visible room temperature	34°C±0.5°C
	UV room temperature	34°C±0.5°C
	Raster scribing	3600 lines/mm
	Spectral range	165~580nm
	Average resolution	≤10pm/pixel
	Visible focal length	300mm
	Ultraviolet focal length	298mm
Excitation source	Light source	high energy excitation light source
	Frequency	100~1000Hz
	Excitation voltage	300V
	Excitation current	400A
Excitation stand	Gas supply	argon (purity≥99.9995%, pressure: ≥0.3MPa)
	Flow rate	excitation: 3L/min, standby: 0.3L/min
	Electrode	tungsten electrode
	Purge	automatic cleaning
	Design	self-compensating thermal deformation design
	Analysis interval	2.8mm
Analysis software	<ul style="list-style-type: none"> <li>•automatic calibration control according to the given deviation and number of excitations</li> <li>•the analyzed results show the percentage, light intensity values, intensity ratios</li> <li>•electrode cleaning according to set data, display and corresponding deviation</li> <li>•ability to store and print test element results</li> </ul>	
Transmission	DM9000A-based ethernet data transmission	
Work hours	standby: 10h, continuous excitation: 160~180 times	
Work environment	5~35°C	
Power supply	replaceable lithium battery, 24V	
Dimension (LxWxH)	840×700×1050mm	
Weight	50kg	

## IRON BASE CURVES

Curve number	A1	A2	A3	A4	A5	A6	A7
Elemental content (%)	Low alloy steel	Cr/Ni stainless steel	High speed tool steel	High Mn steel	High Cr cast iron*	High Ni cast iron*	Cast iron*
C	0.006-1.3	0.008-2.5	0.08-2.2	0.5-2.4	0.9-3.4	1.2-3.8	1.8-4.5
Si	0.01-2.9	0.09-4.0	0.04-1.5	0.3-1.7	0.2-2.5	0.04-3.5	0.2-4.2
Mn	0.03-14	0.12-16	0.04-1.7	5.3-23	0.1-2.4	0.001-6.8	0.06-4.7
P	0.002-0.12	0.003-0.3	0.004-0.007	0.01-0.2	0.01-0.3	0.0015-0.56	0.02-0.8
S	0.002-0.46	0.001-0.4	0.001-0.06	0.006-0.11	0.01-0.15	0.0015-0.24	0.003-0.2
Cr	0.01-12.5	7.4-32	1.8-8.1	0.08-3.8	0.4-34	0.0015-9.1	0.03-2.8
Ni	0.004-4.4	0.8-40	0.07-0.55	0.04-3.5	0.05-2.75	0.9-36.6	0.05-5.1
Mo	0.004-1.76	0.08-4.2	0.02-9.4	0.1-2.0	0.1-4	0.0015-1.5	0.01-2.1
Al	0.003-0.5	0.005-1.7	0.005-1.6	0.008-0.12	-	-	0.002-0.25
Cu	0.002-0.7	0.05-4.5	0.04-0.5	0.02-0.6	0.06-1.5	0.005-0.3	0.06-2.0
Co	0.001-0.5	0.008-0.62	0.008-16	0.007-0.1	-	-	0.008-0.03
Ti	0.002-0.5	0.005-1.1	-	0.004-0.4	0.01-0.14	-	0.007-0.7
Nb	0.002-0.53	0.02-2.0	-	0.08-0.42	0.1-0.7	0.003-0.38	0.002-0.7
V	0.003-0.9	0.02-0.58	0.03-2.5	0.01-0.84	0.02-1.2	-	0.01-0.7
Ca	-	-	-	-	-	-	-
B	0.006-0.02	0.007-0.02	-	-	-	-	0.002-0.3
Sn	0.001-0.09	0.003-0.05	-	-	-	-	0.003-0.3
As	0.001-0.1	0.004-0.04	-	-	-	-	0.008-0.09
Sb	0.002-0.02	-	-	-	-	-	0.004-0.2
Fe	REF	REF	REF	REF	REF	REF	REF

\*Cast iron samples need to be whitened samples

## ALUMINUM BASE CURVES

Curve number	B1	B2	B3	B4	B5
Elemental content (%)	Al low alloy	Al-Si alloy	Al-Zn alloy	Al-Cu alloy	Al-Mg-Si alloy
Si	0.01-1.63	0.02-24	0.02-9.4	0.02-7	0.02-2.3
Fe	0.01-1.65	0.02-4	0.03-1	0.05-1.9	0.07-0.80
Cu	0.002-1	0.005-6	0.01-4.3	0.01-13	0.07-1
Mn	0.001-1	0.005-1	0.02-1	0.05-1	0.03-2.4
Mg	0.002-1	0.01-1.5	0.01-4	0.01-2.7	0.006-10.2
Cr	0.001-0.15	0.005-0.5	0.01-0.4	0.01-0.14	0.01-0.4
Ni	0.001-0.16	0.02-2.5	0.01-0.2	0.01-2.3	0.005-0.25
Zn	0.002-0.5	0.005-3.5	0.01-12	0.05-3.5	0.01-1
Ti	0.001-0.15	0.005-0.4	0.005-0.3	0.001-0.2	0.007-0.3
Ca	-	0.002-0.03	-	-	-
Cd	0.01-0.3	0.001-0.3	0.002-0.3	0.01-0.3	0.01-0.3
Ga	0.002-0.06	0.005-0.2	-	-	0.009-0.02
Pb	0.02-0.5	0.005-0.5	0.005-0.5	0.01-0.5	0.001-0.5
Sb	-	0.005-0.4	-	-	-
Sn	0.01-0.2	0.003-0.5	0.005-0.2	0.02-0.3	0.007-0.2
V	0.004-0.05	0.005-0.2	0.005-0.03	0.01-0.03	0.002-0.03
Zr	0.001-0.12	0.005-0.2	0.01-0.3	0.001-0.2	0.003-0.12
P	-	0.002-0.005	-	-	-
Al	REF	REF	REF	REF	REF

## COBALT BASE CURVES

Curve number	C1	C2	C3	C4	C5	C6	C7
Elemental content (%)	Brass	Copper	Al-Cu alloy	Beryllium bronze	Sn-Pb-Cu alloy	Pure copper	Si-Bronze
Zn	0.5-43.0	0.01-23.0	0.04-2.2	0.005-0.23	0.003-0.7	0.001-0.3	0.2-6.0
Pb	0.01-6.0	0.002-0.13	0.002-0.068	0.005-0.3	0.001-21	0.001-1.5	0.01-0.8
Sn	0.009-4.8	0.009-0.13	0.003-0.35	0.005-0.18	0.005-11.2	0.001-0.3	0.05-0.7
P	0.002-0.14	0.003-0.07	-	-	0.001-0.42	0.001-0.078	0.005-0.08
Mn	0.001-5.3	0.009-1.1	0.001-3.1	-	0.001-0.4	0.001-0.1	0.2-1.8
Fe	0.02-3.0	0.03-1.03	0.005-6.0	0.02-0.28	0.003-0.028	0.001-0.2	0.1-1.7
Ni	0.009-1.8	5.5-32.5	0.005-6.0	0.005-0.35	0.001-1.0	0.001-0.5	0.05-1.0
Si	0.001-4.6	0.009-0.46	0.004-0.3	0.02-0.3	0.002-0.009	0.001-0.055	1.5-5.0
Mg	0.001-0.01	0.003-0.14	-	0.003-0.7	-	0.001-0.01	-
Cr	0.001-0.2	-	-	-	-	0.001-0.081	-
As	0.001-0.2	0.003-0.05	-	-	0.004-0.2	0.005-0.3	-
Sb	0.001-0.4	0.001-0.012	-	-	0.001-0.6	0.005-0.35	0.005-0.07
Ag	-	-	-	-	0.001-0.14	0.006-0.13	-
Co	0.004-0.1	-	-	-	0.001-0.1	-	-
Al	0.001-6.7	-	3.0-12.9	0.02-0.2	0.01-0.1	-	-
S	0.001-0.15	0.004-0.06	-	-	0.001-0.14	0.001-0.05	-
Cu	REF	REF	REF	REF	REF	REF	REF