


GRINDER AND POLISHER  
CODE MLP-GP260



- ABS case and stainless steel parts, anti-corrosion, easy to clean
- Can hold up to 4 samples(6 holes are optional and can hold up to 6 samples)
- Smooth rotation, low noise
- Adjustable speed
- Water cooling device and abrasive cleaning nozzle prevent samples from overheating and destroying structure
- Platen rotation direction can be selected
- Replaceable platen



silicon carbide paper (optional)



polishing cloth (optional)

SPECIFICATION

|                           |   |
|---------------------------|---|
| Platen diameter           | Ø250mm  |
| Platen rotation speed     | 50~999r/min(stepless adjustable), 150 or 300r/min(two fixed speeds) |
| Platen rotation direction | clockwise or counterclockwise                                       |
| Grinding head speed       | 50~150r/min(stepless adjustable)                                    |
| Pressure range            | 5~60N   |
| Operating time            | 5~995s  |
| Sample diameter           | Ø30mm(can be customized)  |
| Air pressure              | 0.6~0.9MPa  |
| Power supply              | AC 220V, 50Hz   |
| Input power               | 1.1kW   |
| Dimension                 | 594×795×687mm   |
| Weight                    | 98kg  |

STANDARD DELIVERY

|                       |                        |
|-----------------------|------------------------|
| Main unit             | 1 pc                   |
| Silicon carbide paper | 6 pcs (200, 600, 1000) |
| Polishing cloth       | 4 pcs                  |

OPTIONAL ACCESSORY

| Description             | Code           | Specification  |
|-------------------------|----------------|--|
| Silicon carbide paper   | MLP-GP260-Sxx* | 50 pcs/box, select granularity: 120, 180, 240, 400, 600, 800, 1000, 1200, 1500, 2000               |
| Polishing cloth         | MLP-GP260-CLT  | 15 pcs/box, long velvet silk material  |
| Diamond Polishing agent | MLP-GP260-Dxx* | 500ml, select granularity(μm): W40, W28, W20, W14, W9, W7, W5, W3.5, W2.5, W1.5, W1.0, W0.5, W0.25 |

\* xx is granularity specification, for example, code **MLP-GP260-D40** stands for diamond polishing agent 40μm granularity.